MSDS # 45001-A

Section One: Identification

Sanford, L.P. 2707 Butterfield Road Oak Brook, IL 60523 USA 800-323-0749 or 630-481-2000 **EMERGENCY MEDICAL NUMBER:** 

888-786-0972

Product Name: Office Depot Multi-Purpose White Correction Fluid

## Section Two: Hazard Identification

WARNING: FLAMMABLE. PRECAUTIONS: Do not store or use near heat or flame. KEEP OUT OF REACH OF CHILDREN.

Section Three: Composition

Titanium dioxide (13563-67-7), solvent naphtha (64742-89-8), mineral spirits (64742-48-9), resins, dispersant, colorants, fragrance

Section Four: First Aid Measures

Inhalation: This product is considered safe under normal use conditions.

Skin Contact: Wash with soap and water.

Eye Contact: Irritation may occur. Wash throughly with water.

Ingestion: Contact a physician. NOTE TO PHYSICIAN: Contains solvent naphtha and mineral spirits, which may cause chemical

pneumonitis.

Section Five: Fire Fighting Measures

Flash Point: 27F (Closed Cup)

Flammability Limits (% by volume): Lower: 1% Upper: 8%

Extinguishing Media: Dry chemical, foam, carbon dioxide.

Special Fire Fighting Measures: In fires involving large quantities, use self-contained breathing apparatus. Cool fire-exposed containers with

water spray/fog.

Unusual Fire and Explosion Hazards: Product is flammable. May produce hazardous decomposition products.

Section Six: Accidental Release Measures

In Case of Spill or Accidental Release: Wipe up with absorbent material.

Section Seven: Handling and Storage

Handling: Do not store or use near heat or flame.

Storage: In large quantities, store in a well-ventilated area.

Section Eight: Exposure Controls and Personal Protection

Eye Protection: None under normal use conditions.

Clothing: None under normal use conditions.

Respirator: None under normal use conditions.

Ventilation: None under normal use conditions.

February 1, 2007 Page 1 of 2

Section Nine: Physical and Chemical Properties

For product unless otherwise specified:

Boiling Point: 209 - 230F Specific Gravity: ~1.2

Vapor Pressure: 124 mm Hg at 100F

Solubility in Water: Negligible

Evaporation Rate: 3.6 (butyl acetate = 1)

Appearance/Odor: White fluid; solvent odor

Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Open flames or other ignition sources.

Chemical Incompatibility: Strong oxidizers

Hazardous Decomposition: May produce oxides of carbon, nitrogen, and various hydrocarbons in fire.

Hazardous Polymerization: Will not occur

Section Eleven: Toxicological Information

See Section Two: Hazard Identification for any hazards

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen: Transport Information

DOT: ORM-D Consumer Commodity

IATA: Consumer Commodity, 9, ID8000

IMO: UN1993, NOS(Petroleum Distillates), Class 3, PGII, Ltd. Qtys. IMDG Emergency Code: EmS#3-07

Section Fifteen: Regulatory Information

TSCA: The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory.

All ingredients used to manufacture this product are listed on the TSCA Inventory

Section Sixteen: Other Information

**HMIS Code** 

Health 2
Flammability 3
Reactivity 0
Personal Protection N/A

Sanford has been advised by Counsel that the OSHA Hazard Communication Standard does not apply to the Sanford Product described in this Material Safety Data Sheet. The reason for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2006 per the Code of Federal Regulations. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by the Hazard Communication Standard nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard.

0=Minimal / 4 = Severe

February 1, 2007 Page 2 of 2